



## OMAN Endurance Protect C3 5W40

### Description

Endurance Protect C3 is a universal synthetic motor oil, developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

Endurance Protect C3 5W40 is a universal synthetic motor oil, specially developed for passenger cars with unit injector diesel engines. Moreover, this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.

### Specifications

ACEA A3/B4/C3-16 | API SN/CF | BMW Longlife-04 | MB 229.31 | Dexos 2 | FIAT: 9.55535-GH2/S2 | FORD WSS-M2C917-A | PORSCHE A40 | RENAULT RN 0700/0710 | VW 502.00/505.00/505.01

### Typical Characteristics

|                      |                    |      |
|----------------------|--------------------|------|
| Density at 15°C      | kg/m <sup>3</sup>  | 852  |
| Kin. viscosity 40°C  | mm <sup>2</sup> /s | 85   |
| Kin. viscosity 100°C | mm <sup>2</sup> /s | 13.9 |
| Viscosity Index      |                    | 168  |
| Flash Point COC      | °C                 | 232  |
| Pour Point           | °C                 | -39  |
| Total Base Number    | mgKOH/g            | 7.6  |
| Sulphate Ash         | %                  | 0.81 |

Version : 1.0

Date : October 2020

Mentioned product values are indicative typical values. Oliemaatschappij Anglo Nederland B.V. can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.