



OMAN MIXEDFLEET SUPER 15W40

Description

Mixedfleet Super 15W40 is formulated with unique low SAPS high performance additives in combination with special selected base oils. This multigrade engine oil fulfills the latest requirements of OEM's for use in high speed four stroke diesel engines of the latest models and has the following properties:

- meets or exceeds the requirement of the nowadays low emission standards
- an excellent cold start properties
- a very good shear stability
- an improved oxidation resistance
- a very strong dispersion, therefore the deposits and sludge are restricted to a minimum
- excellent properties against wear, corrosion and foam
- a lower oil consumption

Application

Mixedfleet Super 15W40 is suitable for use in both on-road and off-highway applications. This engine oil contributes to low exhaust emission and particle levels benefits highly to the lifetime of emission control systems. The product complies with and exceeds the requirements of API CJ-4 (European and North American engines manufacturers). Product can be used in engines with or without Diesel Particle Filter(DPF) and for most engines with Exhaust Gas Recirculation (EGR) and Selective Catalytic Reduction (SCR) after treatment systems. Suitable for Euro 1,2,3,4,5,6* engines.

**Euro 6 oil recommendations differ per truck brand. Check owner's manual before use.*

Specifications

API SN/CJ-4 | ACEA E9 | Cummins CES 20081 | Cat ECF-3/2 | Deutz DQC III-10-LA | Detroit Diesel 93K218
MAN M 3575 | MB 228.31 | MTU Type 2.1 | Mack EO-O PP | Renault VI RLD-3 | Volvo VDS-3/4

Typical Characteristics

Density at 15 °C,	kg/l	0,874
Viscosity 40 °C,	mm ² /s	115
Viscosity 100 °C,	mm ² /s	15,1
Viscosity Index		136
Flash Point COC,	°C	238
Pour Point,	°C	-39
Total Base Number,	mg KOH/g	8.3
Sulphate Ash,	%	1,02

Version : 1.0

Date : October 2020