

OMAN SYNTRAC FE LOW SAPS 5W30 PLUS

Description

Syntrac FE Low Saps 5W30 Plus is a top quality fuel economy diesel engine oil based on the latest additive technology combined with very special base oils. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against wear, corrosion and foam
- a high and stable viscosity index
- a low sulphated ash number
- prolonged oil drain intervals
- a lower fuel consumption

Application

Syntrac FE Low Saps 5W30 Plus is a top quality fuel saving, synthetic motor oil specially developed for diesel engines under the most severe operating conditions. The oil is widely applicable and is very suitable to use in Euro 4, 5 and 6 motors with or without particulate filters and exhaust gas catalyst. This oil belongs to the group of "low-SAPS" lubricants.

Specifications

ACEA E6, E7, E9 | API CK-4/SN | MB-Approval 228.51 | JASO DH-2/DH-1 | MAN M 3677/M 3477/M 3271-1 | Volvo VDS-3/VDS-4/4.5 | Scania Low Ash | Mack EOS-4.5 | Renault VI RLD-3/RLD-2 | MTU Type 3.1 | Mack EO-M Plus | Cummins CES 20081/86 | Cat ECF-3/2 | Detroit Diesel 93K218/93K222 | Deutz DQC IV-18 LA

Typical Characteristics

Density at 15°C	kg/l	0,855
Viscosity -30°C	mPa.s	6460
Viscosity 40°C	mm²/s	70,20
Viscosity 100°C	mm²/s	11,80
Viscosity Index		165
Flash Point COC	°C	214
Pour Point	°C	-45
Total Base Number	mg KOH/g	9,3
Sulphate Ash	%	0,99

Version: 1.0

Date: October 2020

Mentioned product values are indicative typical values. Oliemaatschappij Anglo Nederland B.V.can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.