



Version : 1
Date : may 20 2014

SYNLUB 2-STROKE

Description

Synlub 2-Stroke is an engine oil formulated with carefully selected high quality mineral and synthetic base oils and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- an active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very effective activity against wear and corrosion
- a very limited formation of smoke
- selfmixing

Application

Synlub 2-stroke is a two stroke engine oil which is advised for the lubrication of high speed aircooled two stroke engines under heavy duty load. This selfmixing two stroke engine oil may also be used for watercooled two stroke engines (radiator type cooling systems).

Specifications

API TC | JASO FD | ISO-L-EGD | Global GD | Husqvarna 272 | 2-Stroke DFI

Typical Characteristics

Density at 15 °C,	kg/l	:	0,864
Viscosity 40 °C,	mm ² /s	:	64,60
Viscosity 100 °C,	mm ² /s	:	9,56
Viscosity Index		:	129
Flash Point COC,	°C	:	116
Pour Point,	°C	:	-25
Total Base Number, mg	KOH/g	:	1,4
Sulphate Ash,	%	:	0,14

Volume	Art.no.
1 ltr	310401
4 ltr	310404
5 ltr	310405
20 ltr	3104020
60 ltr	3104060
208 ltr	31040208
bulk	31040

UTB B.V.

Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.